KØSTER

// Examples for fields of application

Canals



Retention basins



Irrigation basins



KÖSTER at your service – worldwide.











// Contact us

KÖSTER BAUCHEMIE AG Dieselstraße 1–10 · 26607 Aurich Tel.: +49 4941 9709 0 E-Mail: info@koster.eu

www.koster.eu


Follow us on social media:















Key features at a glance

- Bridges joints and large cracks
- · Low friction surface increases water flow
- Higher flow leads to higher hydraulic efficiency
- No cost in expensive joint systems
- Stops leakages reduces water loss to surface evaporation
- High UV resistance ensures long-life with minimum maintenance
- Reduced algae growth on the surface of the membrane

// The product





KÖSTER TPO Aqua 2.5 Geo

Special homogeneous geomembrane for hydraulic works such as dams, canals, and artificial lakes. This 2.5 mm FPO/TPO-PE highly UV resistant membrane is strongly tear resistant and provides an exceptionally flexibility. The back-side with the 500 g polyester ensures an outstanding dimension stability and impact resistance.

KÖSTER TPO Aqua 2.5 Geo complies with:

DIN EN 13361: Geosynthetic barriers - Characteristics required for use in the construction of reservoirs and dams

DIN EN 13967: Flexible sheets for waterproofing Plastic and rubber damp proof sheets
including plastic and rubber basement
tanking sheet

The KÖSTER TPO Aqua 2.5 Geo offers a 20 year product warranty.

Considering the premium quality Made in Germany polymers used in the manufacture of this unique membrane, together with decades of experience, a minimum of 40 years of lifespan can be expected for our membrane.

