

KØSTER

// Application

Installalation on suitable substrates

















// Contact us

KÖSTER BAUCHEMIE AG Dieselstraße 1–10 · 26607 Aurich Tel.: +49 4941 9709 0

E-Mail: info@koster.eu

www.koster.eu

Follow us on social media:












// The system



// Exemplary layer structure

- **1** Substrate (e.g. concrete)
- 2 Insulation level old roof (e.g. EPS)
- **3** Old waterproofing (e.g. bitumen, PVC)
- 4 Renovation insulation board (e.g. MiFa, PIR)
- 5 New waterproofing of KÖSTER TPO, mechanically fastened

Advantages of refurbishing existing buildings

- Preservation of the building fabric, conservation of resources
- Savings for the builder
- $\boldsymbol{\cdot}$ Low risk of water ingress during the renovation

// The products



KÖSTER TPO 1.5 F, 2,0 F loosely laid, mechanically fastened

KÖSTER TPO waterproofing membranes are compatible with bitumen and plasticizers. With a fleece-backed KÖSTER membrane, it is possible to renovate flat roofs under certain conditions and preparations without complete demolition of the structure.



KÖSTER TPO 1.5, 1.8, 2.0 Energetic renovation

With additional insulation / refurbishment insulation panels to level the subsurface and to retrofit energetic measures on the existing roof. For solar systems with load-sharing function.

Without disposal costs and complete reconstruction, in other words, very economical refurbishment variants.

